TEST REPORT

Kunde: *Client:*	Logos Lighting Co., Ltd
Adresse: *Address:*	5th Floor, Building A, Zhixuanhan Yuanling Industrial Park, Shiyan Town, Baoan District, Shenzhen City, Guangdong Province, China 518108
Hersteller: *Manufacturer:*	Logos Lighting Co., Ltd
Adresse: *Address:*	5th Floor, Building A, Zhixuanhan Yuanling Industrial Park, Shiyan Town, Baoan District, Shenzhen City, Guangdong Province, China 518108
Name der Marke: *Brand Name:*	LOGOS LED
Beschreibungdes Produkts: *Product Description:*	LED Street Light
Modelle: *Models:*	See model list on page 3
Bewertung: *Rating:*	See model list on page 3
Verfahren: *Method:*	Clause 9 of IEC 60598-1:2020
Prüfergebnis*: *Test result*:*	Pass

Datum der Prüfung: *Date of Test:*	**Datum der Emission:** *Date of Issue:*	**Klassifizierung:** *Classification:*	**Gegenstand der Prüfung:** *Test item:*
2023/8/24	2025/4/29	Commission Test	IP66 Test

Prüflabor (Testlabor) / Testing Laboratory:
Shenzhen Southern LCS Compliance Testing Co., Ltd.
Room 101-201, Building 39, Xialang Industrial Zone, Heshuikou Community, Matian Street, Guangming District, Shenzhen, Guangdong, China

Test von/Test by:	**Check von/**Check by:	**Genehmigt von/**Approved by:
Yeoh Zhang/ Project Engineer	Torres He/ Director	Jesse Liu/ Manager

Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.

Remark: The duplication of this report or parts of it and its use for advertising purposes is only allowed with permission of the testing laboratory.This report contains the result of examination of the product sample submitted by the applicant. A general statement concerning the quality of the products from the series manufacturer cannot be derived therefore.

General remarks:

1. The test results presented in this report relate only to the object tested.
2. This report shall not be reproduced, except in full, without the written approval of the Issuing Testing Laboratory. The authenticity of this Test Report and its contents can be verified by contacting the Testing Laboratory, responsible for this Test Report.
3. The general information of applicant and manufacturer (such as the name and address), product name, model/type reference, trademark and other similar information contained in this report are all provided by the applicant, the laboratory is not responsible for verifying its authenticity.

Modified Information

Version	Report No.	Revision Date	Summary
--	LCSB050823088S	/	Original Version
V1.0	LCSB04015068S	2025-04-29	Co-license

The declaration of identity dated 2025-04-29 from applicant confirm this:
The "LED Street Light" model "LGS-SLAU-50W,LGS-SLAU-100W,LGS-SLAU-150W,LGS-SLAU-200W, LGS-SLSE-50W,LGS-SLSE-60W,LGS-SLSE-80W,LGS-SLSE-100W,LGS-SLSE-120W,LGS-SLSE-150W, LGS-SLSE-180W,LGS-SLSE-200W,LGS-SLIR-30W,LGS-SLIR-50W,LGS-SLIR-60W,LGS-SLIR-80W, LGS-SLIR-100W,LGS-SLIR-150W,LGS-SLIR-200W" of co-license holder "Name:Logos Lighting Co., Ltd. " "Address: 5th Floor, Building A, Zhixuanhan Yuanling Industrial Park, Shiyan Town, Baoan District, Shenzhen City, Guangdong Province, China 518108"is the same "****" model "****" of license holder "Name:****" "Address:****".(****:hided by commercial reason)
Existing approved test report "LCSB050823088S" dated 2023/8/24. This co-license test report is based on the test raw-data of existing approved test report, after construction/information review and verification, no additional tests were considered necessary.

Equipment used during test:

ID Number	Instrument	Model/ Type	Calibration Date
SLCS-S-031	Sand and dust test box	SG-500	2023-05-09
SLCS-S-034	IPX5, IPX6 waterproof equipment	JL-1/2	2023-05-09
SLCS-S-135	Digital hygrometer thermometer	HTC-1	2023-05-09
SLCS-S-072	Torque Driver	26RTD	2023-05-08
SLCS-S-073	Hi-pot tester	AN9602M	2023-05-09
SLCS-S-062	Frequency Converter	AN97020TS	2023-05-09
SLCS-S-059	Digital Power Metal	PF9800	2023-05-09

General product information:

- Unless otherwise specified, the models LGS-SLIR-200W was chosen as representative model to perform all test.
- AC 100-240V, 50/60Hz

Model list:

Model No.	Power (W)	LED driver model No.
LGS-SLIR-30W	30	ZH-WP-40H-130
LGS-SLAU-50W	50	ZH-WP-60H-130
LGS-SLIR-50W	50	
LGS-SLSE-50W	50	
LGS-SLSE-60W	60	
LGS-SLIR-60W	60	
LGS-SLSE-80W	80	ZH-WP-80H-130
LGS-SLIR-80W	80	
LGS-SLAU-100W	100	ZH-WP-120H-150
LGS-SLIR-100W	100	
LGS-SLSE-100W	100	
LGS-SLSE-120W	120	
LGS-SLAU-150W	150	ZH-WP-160H-150
LGS-SLIR-150W	150	
LGS-SLSE-150W	150	
LGS-SLSE-180W	180	ZH-WP-200H-260
LGS-SLAU-200W	200	
LGS-SLSE-200W	200	
LGS-SLIR-200W	200	

Test Item:

Tests for protection against dust-proof: IP6X

Test Method:

The tests should be carried out under the standard atmospheric condition.

Temperature range: 20°C to 30°C

Dust-proof luminaires (first characteristic IP numeral 6) shall be tested in a dust chamber similar To that shown in Figure 2, in which talcum powder is maintained in suspension by an air current.

The chamber shall contain 2 kg of powder for every cubic metre of its volume. The talcum powder used shall be able to pass through a square-meshed sieve whose nominal wire diameter is 50 μmand whose nominal free distance between wires is 75 μm. It shall not have been used for more than 20 tests.

The test shall proceed as follows.

The luminaire is suspended outside the dust chamber and operated at rated supply voltage until operating temperature is achieved.

a) The luminaire, whilst still operating, is placed with the minimum disturbance in the dust chamber.

b) The door of the dust chamber is closed.

c) The fan/blower causing the talcum powder to be in suspension is switched on.

d) After 1 min, the luminaire is switched off and allowed to cool for 3 h whilst the talcum powder remains in suspension.

NOTE: The 1 min interval between switching on the fan/blower and switching off the luminaire is to ensure that the talcum powder is properly in suspension around the luminaire during initial cooling, which is most important with smaller luminaires. The luminaire is operated initially as in item a) to ensure the test chamber is not overheated.

Acceptance Conditions:

After completion of the tests, the luminaire shall withstand the electric strength test specified in Section 10,and inspection shall show:No deposit of talcum powder inside enclosures for dust-tight luminaires.

Test Result:

☒ **Pass** ☐ **Fail**



NOTE See IEC 60068-2-68, figure 2 valid for La2 only.

Figure 2 – Test device to verify protection against dust (dust chamber)

Test Item:
Tests for protection against ingress moisture: IPX6
Test Method:
The tests should be carried out under the standard atmospheric condition.
Temperature range: 20℃ to 30℃.
Powerful water jet-proof luminaires (second characteristic IP numeral 6) are switched off and immediately subjected to a water jet for 3 min from all directions by means of a hose having a nozzle with the shape and dimensions shown in Figure 8. The nozzle shall be held 3 m away from the sample.
The water pressure at the nozzle shall be adjusted to achieve a water flow rate of 100 l/min ± 5 % (approximately 100 kN/m2).
Before the tests for the second characteristic numeral, with the exception of IPX8, the luminaire complete with lamp(s) shall be switched on and brought to a stable operating temperature at rated voltage.
The water for the tests shall be at a temperature of 15 °C ± 10 °C
Luminaires shall be mounted and wired as in normal use and placed in the most unfavourable position, complete with their protective translucent covers, if any, for the tests of IP.
Where connection is made by a plug or a similar device, then this shall be regarded as part of the complete luminaire and shall be included in the tests and similarly for any separate controlgear.
For tests of IP, fixed luminaire intended for mounting with its body in contact with a surface shall be tested with an expanded metal spacer interposed between the luminaire and the mounting surface. The spacer shall be at least equal in overall size to the projection of the luminaire, and have dimensions as follows:

Longway of mesh	10 mm	to	20 mm
Shortway of mesh	4 mm	to	7 mm
Strand width	1,5 mm	to	2 mm
Strand thickness	0,3 mm	to	0,5 mm
Overall thickness	1,8 mm	to	3 mm

Luminaires having provision for draining water by means of drain holes shall be mounted with the lowest drain hole open unless otherwise specified in the manufacturer's installation instructions.
If the installation instructions indicate that a luminaire is for ceiling or under-canopy mounting, the luminaire shall be attached to the underside of a flat board or plate which extends 10 mm beyond that part of the luminaire perimeter in contact with the mounting surface
For recessed luminaires, the parts in the recess and the parts protruding from the recess shall each be tested according to their IP classification as indicated in the manufacturer's mounting instructions.
A box encapsulating the part in the recess may be necessary for the test of IP.
Note: Portable luminaires, wired as in normal use, shall be placed in the most unfavourable position of normal use.
Glands, if any, shall be tightened with a torque equal to two-thirds of that applied to glands in the test of 4.12.5.
Fixing screws of covers, other than hand-operated fixing screws of glass covers, shall be tightened with a torque equal to two-thirds of that specified in Table 4.1.
Screwed lids shall be tightened with a torque having a value in newton metres numerically equal to

one-tenth of the nominal diameter of the screw thread in millimetres. Screws fixing other caps shall be tightened with a torque equal to two-thirds of that specified in Table 4.1.

Acceptance Conditions:

After completion of the tests, the luminaire shall withstand the electric strength test specified in Section 10, and inspection shall show:

no trace of water on electrical connections, current carrying parts or on insulation where it could become a hazard for the user or surroundings, for example where it could reduce the creepage distances below the values specified in Section 11; the only exception to this is for SELV conductors where the voltage under load does not exceed 12 V r.m.s. or 30 V ripple free d.c. and the conductors are protected from corrosion.

For luminaires without drain holes, there shall be no water entry.

For luminaires with drain holes, water entry including condensation is allowed during the tests if it can drain out effectively and provided it does not reduce the creepage and clearance distances below the minimum levels specified in the standard

Test Result:

☒ **Pass** ☐ **Fail**



D' = 6,3 mm for the test of 9.2.6 (second characteristic numeral 5)
D' = 12,5 mm for the test of 9.2.7 (second characteristic numeral 6)



Dimensions in millimetres

Figure 8 – Nozzle for spray test

Table 4.1 – Torque tests on screws

Nominal outer thread diameter of screw mm	Torque Nm		
	1	2	3
Up to and including 2,8	0,20	0,40	0,40
Over 2,8 up to and including 3,0	0,25	0,50	0,50
Over 3,0 up to and including 3,2	0,30	0,60	0,50
Over 3,2 up to and including 3,6	0,40	0,80	0,60
Over 3,6 up to and including 4,1	0,70	1,20	0,60
Over 4,1 up to and including 4,7	0,80	1,80	0,90
Over 4,7 up to and including 5,3	0,80	2,00	1,00
Over 5,3 up to and including 6,0	–	2,50	1,25
Over 6,0 up to and including 8,0	–	8,00	4,00
Over 8,0 up to and including 10,0	–	17,00	8,50
Over 10,0 up to and including 12,0	–	29,00	14,50
Over 12,0 up to and including 14,0	–	48,00	24,00
Over 14,0 up to and including 16,0	–	114,00	57,00

Table 4.2 – Torque tests on glands

Diameter of test rod mm	Moment	
	Metal glands Nm	Moulded plastic glands Nm
Up to 7	6,25	2,5
Over 7 up to 14	6,25	3,25
Over 14 up to 20	7,50	5
Over 20	10	7,50

Withstand the electric strength after IP6X test:		
Test Location	Test Voltage	Broken or Flashover
Live parts and accessible parts for model LGS-SLIR-200W	1480V	☐Yes ■No
Withstand the electric strength after IPX6 test:		
Live parts and accessible parts for model LGS-SLIR-200W	1480V	☐Yes ■No

Photo Documentation:

Photo 1: Overall view of model LGS-SLIR-200W



Photo 2: Overall view of model LGS-SLIR-200W

----- End of Test Report-----